


N.rev. / Rev. N.		Descrizione / Description		Data / date	Firma / Sign	Contr. da / Ckd. by	
<p>EVO3 Pro - 22 pins Deutsch connector harness</p>							
					<p>5 pins Binder 712 female connector pinout Solder termination view</p>		
					<p>4 pins Binder 719 female connector pinout Solder termination view</p>		
				<p>SEZ A-A</p>	<p>22 pins Deutsch male connector pinout Contact insertion view</p>		
Rif. / Ref.	Q.tà / Q.ty	Materiale / Material		N. articolo / Item N.			
Progettato da / Designed by	Contr. da / Ckd. by	Approvato da / Approved by	Nome file / File name	Data / Date	Scala / Scale		
LI							
		<p>Titolo / Title Cavo EVO3 Pro - 22 pins Deutsch connector harness</p>					
		<p>N. disegno / Drawing N. 04.549.53</p>		<p>Rev. / Rev. 5</p>	<p>Foglio / Sheet 1 of 2</p>		

N.rev. / Rev. N.	Descrizione / Description	Data / date	Firma / Sign	Contr. da / Ckd. by
------------------	---------------------------	-------------	--------------	---------------------

Table 1 - Channels cabled with connectors							
22 pins Deutsch connector pin	Cable colour	Destination connector	Destination connector pin	Cable type	Lenght	Channel	Label
7 9 8 n.c.	white black red bleu	Binder USB	1 2 3 4	4x0.35 mm ²	1100 mm	USB D+ GND USB D-	USB
5 11 10 n.c.	white black red bleu	Binder Speed 3	1 2 3 4	4x0.35 mm ²	300 mm	Speed 3 GND V battery	Speed 3
6 11 10 n.c.	white black red bleu	Binder Speed 4	1 2 3 4	4x0.35 mm ²	300 mm	Speed 4 GND V battery	Speed 4
4 2 13 3	white black red bleu	Binder Exp.	1 2 3 4	4x0.35 mm ²	350 mm	CAN 0+ GND V battery CAN 0-	Exp.
14 2 14 1	white black red bleu	Binder gear flash	1 2 3 4	4x0.35 mm ²	350 mm	Gear flash GND gea flash V battery	Gear flash

Table 2 - Channels cabled without connector					
22 pins Deutsch connector pin	Cable colour	Not cabled channel	Cable type	Lenght	Channel
15 12	white black	Digit input 1 (not used)	1x0.5 mm ² 1x0.5 mm ²	550 mm	IN 1 GND
16 12	yellow black	Digit input 2 (not used)	1x0.5 mm ² 1x0.5 mm ²	550 mm	IN 2 GND
20 19 21	white black bleu	CAN	1x0.5 mm ² 1x0.5 mm ² 1x0.5mm ²	550 mm	CAN 1+ GND CAN 1-
17 19 18	white black bleu	RS232	1x0.5 mm ² 1x0.5 mm ² 1x0.5 mm ²	550 mm	RS232 RX GND RS232 TX

Rif. / Ref.	Q.tà / Q.ty	Materiale / Material		N. articolo / Item N.		
Progettato da / Designed by LI		Contr. da / Ckd. by	Approvato da / Approved by	Nome file / File name	Data / Date	Scala / Scale
			Titolo / Title EVO3 Pro – 22 pins Deutsch connector harness			
			N. disegno / Drawing N. 04.549.53		Rev. / Rev. 5	Foglio / Sheet 2 of 2